

Tragfähigkeitstabelle

Table of WLL

Farben	ein Hebebänder One Doublex Flat Sling					zwei Hebebänder Two Doublex Flat Slings			
	direkt kg	geschürzt kg	umgelegt, umschlungen kg			direkt kg	geschürzt kg	direkt kg	geschürzt kg
	0°	0° **	0° *	bis 45°	45°- 60°	bis 45°		45°- 60° **	
									
violett	1.000	800	2.000	1.400	1.000	1.400	1.120	1.000	800
grün	2.000	1.600	4.000	2.800	2.000	2.800	2.240	2.000	1.600
gelb	3.000	2.400	6.000	4.200	3.000	4.200	3.360	3.000	2.400
grau	4.000	3.200	8.000	5.600	4.000	5.600	4.480	4.000	3.200
rot	5.000	4.000	10.000	7.000	5.000	7.000	5.600	5.000	4.000
braun	6.000	4.800	12.000	8.400	6.000	8.400	6.720	6.000	4.800
blau	8.000	6.400	16.000	11.200	8.000	11.200	8.960	8.000	6.400
orange	10.000	8.000	20.000	14.000	10.000	14.000	11.200	10.000	8.000
diverse	12.000	9.600	24.000	16.800	12.000	16.800	13.440	12.000	9.600
diverse	16.000	12.800	32.000	22.400	16.000	22.400	17.920	16.000	12.800
orange	20.000	16.000	40.000	28.000	20.000	28.000	22.400	20.000	16.000
orange	24.000	19.200	48.000	33.600	24.000	33.600	26.880	24.000	19.200

*) Abweichungen durch Handhabungstoleranzen bis 7° zulässig.

**) Für die Anschlagart „geschürzt“ dürfen nur Schlaufenbänder mit Verstärkung in der Schlaufe verwendet werden.

Der Öffnungswinkel der Schlaufe maximal 20°!

